

“IDEAL FOR FARM USE”

Brown Bear’s Line Of Tractor And Skidsteer Mounted Composters

Brown Bear composters mount to any tractor with Cat II or III 3-pt. hitches with 540 rpm pto speed and 85-130 pto hp or 1,000 rpm pto speed and 100-160 pto hp. Users say they’re easy to operate and maintain.

For use in multiple farm applications:

Feedlots - Manure and pen scrapings are hauled to a windrow site where the Brown Bear aerator is used to windrow and aerate the manure at the same time. The manure, or manure and bedding mix, starts the composting process at about 70% moisture and continues to about 10% moisture. Windrows are turned twice a week for the first couple weeks, then once a week for the next couple of weeks until the compost process has broken down the manure to a rich odor and pathogen free soil like texture. The aerator can also be used in the pens to dry out the manure and to move snow away from the bunk lines.

Dairies - Manure from dry lot scraping or from manure separators can be windrowed and aerated to produce finished compost. While the dry lot scrapings are composted much like the feedlot manure, manure from a manure separator or press can be composted to produce sterile bedding. Once manure is flushed from the free stall and milking areas to a manure separator, the solids from the separator are stockpiled on a hard surface pad for a few days to allow for further gravity separation of the free water. The liquids from the separator and manure gravity separation

may be lagooned for land application. The solids are carried from the gravity separation pad at about 15% solids to a compost pad which is generally compacted clay, but in some cases may be hard surfaced. Once there the manure is placed in windrows and within a day or so the temperatures of the windrows will reach 140-180 degrees F. The windrows are aerated with the Brown Bear attachment twice per week for a period of 30 days until tests indicate that the manure is sterile and 80-90% solids when it is then used as recycled bedding under the cows. Tests indicate that the compost has less indicator organisms than wood chips or sawdust and SCC generally goes down when substituting compost in place of wood waste as bedding.

Poultry - Manure from both layer and broiler operations as well as the mortalities from both types of operations is composted using Brown Bear aerators.

Layer manure can be composted in the pit of high rise layer houses using the smaller skid steer composting attachments. Composting of layer manure reduces or eliminates flies, odors and rodents while it reduces volume and moisture and granulates the manure to something easily transported and land applied.



Litter from broiler houses can be recycled by composting within the house to pulverize, decake, sterilize and flash off the ammonia all in one operation, within a few days’ time. Recycling the litter reduces the need to purchase new litter as wood shavings or sawdust, reduces production costs and also eliminates some of the litter application to land in areas of difficult land application. Flocks do better on recycled composted litter showing less mortalities, less blinding, increased feed conversion and increased bird weight at harvest.

Contact: FARM SHOW Followup, Brown Bear Corp., P.O. Box 29, Corning, Iowa 50841 (ph 641-322-4220; fax 641-322-3527; email: sales@brownbearcorp.com; website: www.brownbearcorp.com).

Reader Inquiry No. 139

Hydraulic Drive For Grain Bins

“We’ve eliminated power lines, wiring, electric motors and starters, and all the pulleys and mounts needed to outfit an unloading auger for electric drive,” says Wayne Niewold, of Hydra Fold Auger, Inc., manufacturer of a handy go-anywhere hydraulic unloading drive unit. “It’s great for handling grain in remote locations without electricity,” he points out.

The drive is designed to run off tractor hydraulics of a minimum 10 gpm at 1,000 psi. It features variable speed which can be started, stopped and varied with one valve, helping prevent cracked grain by running the tube, when full, at a slower speed. The drive

unit bolts to the unloading tube with only two bolts. Adjustable brackets for varying lengths of shafts are standard and hubs are available for 1-in., 1 1/4-in., and 1 1/2-in. shafts with machined keyways.

“They’re also easily installed on most any existing unloading auger without removing the bearing and can be plumbed in series with the hydraulic drive on a sweep auger,” says Niewold.

Contact: Hydra Fold Auger, Inc., 931N 1600 E Rd., Loda, Ill. 60948 (ph & fax 217 379-2614 or hydrfoldauger@illicom.net).

Reader Inquiry No. 140



Hydraulic drive easily installs on most any existing unloading auger without removing the bearing.